## signa® 5 whirlpool bath and soaking bath (with 3 tile flange)

the signa<sup>®</sup> whirlpool bath takes its name from the medieval central italian walled city, lastra a signa.



Like the walled city for which it is named, Signa<sup>®</sup> 5 was specially developed and designed for walled surround spaces.

whirlpool bath features:

- Contoured backrest.
- 4 Fully adjustable TheraPro<sup>™</sup> jets
- 2 AccuPro<sup>™</sup> foot jets.
- Exclusive Tru-Level<sup>™</sup> self-leveling base system
- Slip-resistant bottom.
- Patented Fixed Air Flow System
- Drain included on whirlpool baths

# signa<sup>®</sup> 5 with 3 tile flange whirlpool bath

model number: D560 – RH pump, D569 – LH pump

exterior dimensions: 60" long x 42" wide x 22" high

interior dimensions: 41" long x 25" wide

# of Jets/type of Jets: 4 TheraPro<sup>™</sup> Jets 2 AccuPro<sup>™</sup> Back Jets

operating gallons: **42 gallons** 

# signa<sup>®</sup> 5 with 3 tile flange soaking bath

model number: D578 (w/3-tile flange)

exterior dimensions: 60" long x 42" wide x 22" high

interior dimensions: 41" long x 25" wide





## Signa<sup>™</sup> 5 Whirlpool Bath with 3 Tile Flange Model: D560, D569 Signa<sup>™</sup> 5 Bath with 3 Tile Flange Model: D578

### **Ordering Information**


Product Code:

- D560 Signa™ 5 Whirlpool Bath with 3 Tile Flange Right Hand
  D569 Signa™ 5 Whirlpool Bath with 3 Tile Flange Left Hand
- D578 Signa™ 5 Bath with 3 Tile Flange
- Center Drain Location

 Accessories / Hardware: Trip-Lever Drain Kit #X559 Rotary Drain Kit, 26" Cable #8730 TheraPro™ Jet Rings Kit: #D095 AccuPro™ Jet Rings Kit: #P556

#### • Trim Kit Finishes Available:

- (827) Chrome (898) – Brushed Chrome (815) – Satin Nickel (829) – Bright Brass (805) – Platinum
- (826) Brushed Nickel
- (849) Oil Rubbed Bronze



Product Shown: Signa™ 5 Whirlpool Bath with 3 Tile Flange Right Hand Model: D560 \* Measurements inside unit represent cutout in floor to allow for drain/overflow. Minimum Service Access dimensions given.

### Installation Notes

Refer to installation instructions included with fixture before beginning installation. Please confirm product availability and specifications before commencing with any installation work.

PRODUCT SPECIFICATIONS AND AVAILABILITY ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Electrical Components and Electrical Specifications do not apply to non-jetted baths.

## **Technical Specifications**

**Dimensions** 60" L x 42" W x 22" H (1524 mm) L x (1067 mm) W x (559 mm) H

#### Drain/Overflow A: 17-1/2" (445 mm) B: 12-1/2" (318 mm)

**Cutout** Not Applicable

#### Total Weight

D560, D569: 708 lb (321 kg) / 40 lb/sq. ft. (197 kg/m<sup>2</sup>) D578: 667 lb (303 kg) / 38 lb/sq. ft. (186 kg/m<sup>2</sup>)

#### **Operating Gallonage**

42 U.S. Gal. (159 Liters) Max. 82 U.S. Gal. (310 Liters)

### **Product Weight**

D560, D569:108 lb (49 kg) D578: 67 lb (30 kg)

#### **Skirt Mounting**

Optional, U-Frame

Electrical Specifications Models D560, D569 only Requires a dedicated GFCI protected separate circuit. Motor/Pump: 120 VAC, 15 AMP, 60 Hz. RapidHeat™: 120 VAC, 15 AMP, 60 Hz.

Heater (Optional) Models D560, D569 only Requires a dedicated GFCI protected separate circuit. RapidHeat™: P/N S750000

